



ENTRANCE MAT CLEANING & MAINTENANCE

Follow these instructions to prolong the life and professional appearance of your matting:

VACUUM DAILY

DEEP CLEAN PERIODICALLY

Depending on traffic & soil conditions, mats should be cleaned using a hot water extraction cleaning system and a water-based carpet detergent. Follow the manufacturers' directions for using the extraction cleaner and detergent.

DRYING

Remove excess water with a "wet/dry" vacuum or hand the mat to remove excess water.

LOGO CLEANING

Logo inserts can be cleaned with most any waterbased liquid or foam cleaner using a hand held scrub brush to remove surface soil. DO NOT use solvent-based cleaners, rotary scrubbers or other mechanical device to clean logo mats. Use of solvent based cleaners or rotary scrubbers will void the warranty.

STORAGE & HANDLING

Roll clean, dry mat in compact roll around a cardboard core with pile FACING OUT. Store flat, in a cool dry place. DO NOT stand the mat on end or crush it by piling things on top.

REMOVING STAINS

Hand wash the stain using a water based carpet detergent or shampoo.

MATS WITH ANTI-SLIP BACKING

Dragging mats with anti-slip backing may damage the backing. Instead, roll them up and carry the roll.

MATS WITH VELCRO ON BACKING

Mats with Velcro securing them to a carpeted floor should not be lifted abruptly. To move mats with Velcro, roll the mat up slowly to free Velcro from the carpet. Make sure the Velcro is not releasing from the backing. Pick up entire mat to move or reposition.

CAUTION

If the borders on the matting should become broken or curled, remove from service until the tripping hazard can be corrected.

Torn or ripped borders If the vinyl border of the mat is ripped or torn, the damage can usually be repaired by gluing the damaged section together with a cyanoacrylate ester type adhesive.

Curled borders or corners can usually be flattened. Warm the vinyl in the curled area with a hair dryer until the vinyl relaxes and lays flat. DO NOT use a heat gun – excessive heat may damage the vinyl.

THREE YEAR WARRANTY

This yarn fiber is warranted against excessive wear for three years from the date of purchase or installation. Excessive surface wear means more than 10% loss of face pile fiber in any given area.

This limited warranty does not cover cuts, pulls, tears, burns, or vinyl damage due to improper cleaning agent or methods.

See warranty statement for full details.



Split Rock Management, Inc. dba
Vanguard Cleaning Systems of Minnesota
3459 Washington Drive, #109 - Eagan, MN 55122
operations@vanguardcleaningminn.com
Twin Cities 651-379-4000 | Rochester 507-218-3016
vanguardcleaningminn.com
Each Vanguard Cleaning Systems Franchise is independently owned and operated.



05/13/19